

SUN ECON KR-6140

Features KR-6140 is a type of cleaning agent with a lower alkali concentration to meet Japanese regulations. It can be used for cleaning easily damaged molds.

Application For all kinds of rubber mold. Instantly removing the charring pollution occurred by vulcanizing and release agent, in the meantime, red rust will also be removed. Other applications, cleaning agent for plastic injection mold (ultrasound cleaning), carbon removing & degreasing.

Physical Properties Appearance : Light yellow transparent liquid.

Specific gravity : 1.13 (20°C) pH : 13.0(5%) Smell : Non.

- How to Use**
- pour cleaning
 - Pour KR-6140 on the mold at around 100°C, and clean it while scrubbing with a brush, etc.
 - Rinse the mold by pouring water on it.
 - Allow to dry.
 - immersion cleaning.
 - Heat undiluted or diluted KR-6140 in a heatable stainless steel tank. The temperature should be as high as possible.
 - Immerse the mold in the tank and clean for an extended period of time.
 - Pull up the mold and scrub the mold with a brush while spraying it with water.
 - Allow to dry.



During Rinsing

Packing UN 22kg

 +81-3-5687-1931

 sunecon@taiyochem.co.jp

 2-8-11 Higashi-Nihonbashi Chuo-ku, Tokyo

 www.taiyochem.co.jp/